



WALRUS
PUMP

PW Series

Submersible Pump



**Better Life
Through Innovation**

PW-A Series Submersible Pump



50 Hz

Power: 100 ~ 800 W

Head: Up to 14 M

Flow: Up to 440 L/min

Outlet: 1" or 2"

60 Hz

Power: 100 ~ 800 W

Head: Up to 14 M

Flow: Up to 440 L/min

Outlet: 1" or 2"



Product Features

- Submersible pumps for clean water.
- Corrosion-resistant and compact design.
- Motor with thermo overload protection.
- Suitable for cleaning washing towers and other confined spaces pumping use.

Standard Mode

- Model type PW100A R C
 - Function code: ① ②
- R: Available to used in sea fish breeding.
 F: Equipped with float ball level switch.
 C: Equipped with level regulator.
 D: Low suction capability: 1 mm.



Operating Conditions

- Power supply: single-phase 50 or 60 Hz
- Power: 100 W to 800 W
- Insulation class: B
- Protection: IP68
- Length of cable: 4 or 5 M
 10 M (Optional)
- Delivery: up to 440 L/min
- Head: up to 14 M
- Liquids Temperature: 4°C ~ +35°C
- Min. Submerged depth:
PW100A : 7 ±1 cm
PW250A : 9 ±1 cm
PW400A : 10 ±1 cm
PW800A : 12 ±1 cm

Applications

- To be used to circulate water in garden ponds
- To apply to the sprinkler for vegetations of parks.
- To be used in fish breeding ponds.
- To drain the accumulated water from various application field.

Performance Curve



Submersible Pump

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW100A	1"	100	50 60	220 - 240 110 220	1.0 2.0 1.0	6.5	80	155 x 140 x 241	3 x 0.75 x 4	4.1	4.7	72
PW250A	1½"	250	50 60	220 - 240 110 220	2.0 4.0 2.0	9	160	164 x 164 x 350	3 x 1.5 x 5 3 x 1.25 x 5	5.1	5.5	48
PW400A	2"	400	50 60	220 - 240 110 220	3.5 7.0 3.5	10	260	183 x 183 x 382	3 x 1.5 x 5 3 x 1.25 x 5	7.9	8.3	50
PW800A	2"	800	50 60	220 - 240 110 220	6.8 13.4 6.5	14	440	193 x 193 x 412	3 x 1.5 x 5 3 x 2.0 x 5	10.2	10.8	50




Sea Water Pump

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW100AR	1"	100	50 60	220 - 240 110 220	1.0 2.0 1.0	6.5	80	155 x 140 x 241	3 x 0.75 x 4	4.1	4.7	72
PW400AR	2"	400	50 60	220 - 240 110 220	3.5 7.0 3.5	10	260	183 x 183 x 382	3 x 1.5 x 5 3 x 1.25 x 5	7.9	8.3	50
PW800AR	2"	800	50 60	220 - 240 110 220	6.8 13.4 6.5	14	440	193 x 193 x 412	3 x 1.5 x 5 3 x 2.0 x 5	10.2	10.8	50




Float Ball Level Switch

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW100AF PW100ARF	1"	100	50 60	220 - 240 110 220	1.0 2.0 1.0	6.5	80	155 x 140 x 241	3 x 0.75 x 4	4.3	4.9	48
PW250AF	1½"	250	50 60	220 - 240 110 220	2.0 4.0 2.0	9	160	164 x 164 x 350	3 x 1.5 x 5 3 x 1.25 x 5	5.3	5.7	48
PW400AF PW400ARF	2"	400	50 60	220 - 240 110 220	3.5 7.0 3.5	10	260	183 x 183 x 382	3 x 1.5 x 5 3 x 1.25 x 5	8.1	8.5	50




Level Regulator

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW100AC PW100ARC	1"	100	50 60	220 - 240 110 220	1.0 2.0 1.0	6.5	80	227 x 140 x 243	3 x 0.75 x 4	4.6	4.9	48




Low Suction Pump

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW100AD	1"	100	50 60	220 - 240 110 220	1.0 2.0 1.0	6.5	70 80	164 x 164 x 270	3 x 0.75 x 4	4.5	4.5	48
PW250AD	1½"	250	50 60	220 - 240 110 220	2.0 4.0 2.0	9	120	164 x 164 x 350	3 x 1.5 x 5 3 x 1.25 x 5	5.6	6.0	48
PW400AD	2"	400	50 60	220 - 240 110 220	3.5 7.0 3.5	10	130	183 x 183 x 384	3 x 1.5 x 5 3 x 1.25 x 5	8.4	8.8	50


Float Ball Level Switch

Model:
PW100AF / PW100ARF / PW250AF
PW400AF / PW400ARF




Level Regulator

Model:
PW100AC / PW100ARC



Low Suction Pump

Model:
PW100AD / PW250AD / PW400AD



PW-E Series Submersible Pump



Construction Industry



Agriculture/
Fishing Industry



Manufacturing Industry



Wholesale & Retail Industry



Technology Industry



Service Industry



Accommodation & Food Service Activities



WALRUS fit

50 Hz

Power: 250 W

Head: Up to 8 M

Flow: Up to 140 L/min

Outlet: 1½"

60 Hz

Power: 250 W

Head: Up to 9 M

Flow: Up to 140 L/min

Outlet: 1½"



Product Features

- Submersible pumps for clean water.
- Corrosion-resistant and compact design.
- Motor with thermo overload protection.

Standard Mode

- Model type

PW250E	C
--------	---
 - Function code:

1	2
---	---
- C: Equipped level regulator.



Operating Conditions

- Insulation class: B
- Protection: IP68
- Length of cable: 5 M
10 M (Optional)
- Liquids Temperature: 4°C ~ +35°C
- Min.Submerged depth: 9 ±1 cm

Applications

- To be used to circulate water in garden ponds
- To be applicable to the sprinkler for vegetations of parks.
- Watering in the garden and washing car.
- To drain the accumulated water for basement of residence.
- To drain the ground water.
- To drain accumulated water for civil and architecture engineering.

Performance Curve



Submersible Pump

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW250E	1½"	250	50 60	220 - 240 110 220	2.0 4.0 2.0	8 9	140	170 x 150 x 325	$\frac{3 \times 1.5 \times 5}{3 \times 1.25 \times 5}$	5.7	6.2	48




Level Regulator

Model	Outlet In.	Output W	Cycle Hz	Volt V	Amp's A	H max. m	Q max. L/min	Dimensions L x W x H (mm)	Cable Wire C x mm ² x m	N.W. kg	G.W. kg	
PW250EC	1½"	250	50 60	220 - 240 110 220	2.0 4.0 2.0	8 9	140	238 x 150 x 325	$\frac{3 \times 1.5 \times 5}{3 \times 1.25 \times 5}$	6.0	6.5	48

Level Regulator

Model:
PW250EC





WALRUS
PUMP

WALRUS PUMP CO., LTD.

Head office: No.83-14, Dapiantou, Sanzhi Dist.,
New Taipei City 252, Taiwan

Tel: (+886) 2 2636-1123~7

Fax: (+886) 2 8635-2660

Email: walrus.sales@walrus.com.tw



All specifications are subject to change without notice. PW-EN007-202203

