



SERH-50B

Outstanding Features

- Because of the high pressure and flow rate, it is a very suitable pump for sprinkling, first fire fighting and other uses, which require high delivery pressures.
- Of all the high pressure engine pumps in its class, it ensures the highest lift and is a must for sprinklers or for water delivery to high and distant places.

Applications

- Water irrigation sprinkling.
- Irrigation of rice field.
- Orchard cultivation.
- Pumping of well water.
- Feeding water into water reservoir.
- feeding or draining water from pond or troth.
- feeding or draining water from fish farm.
- Washing cattle or barn.
- Washing agricultural tools.

Specifications

Model	SERH-50B	SERH-50
PUMP		
Connection Dia	SUC2" DEL2"	SUC2 1/2" DEL2"
Max Delivery Head	60m	70m
Max Capacity	440 liters/min	600 liters/min
ENGINE		
Model	Forced Air Cooled 4Cycle Gasoline Engine	
	HONDA GX160	HONDA GX240
Set rpm	3900rpm	
Continous Power	3.5kw/3600rpm	5.3kw/3600rpm
Max Power	4.1kw/3600rpm	5.9kw/3600rpm
Gross Weight	30Kg	46kg
Dimension(mm)	415x545x455	578x492x533
Packing Unit	1	1

W. Robinson & Sons (EC) Ltd
 Hainault Business Park
 35-41 Fowler Road
 Ilford, Essex IG6 3WR
 United Kingdom
 Tel : +44-(0)20-8559 6000
 Fax: +44-(0)20-8559 6001
 Email: info@pump.co.uk

